



- FULL RANGE DESIGN
- STRUCTURED PP CONE WITH RUBBER SURROUND
- NEODYMIUM DESIGN,
- STAMPED STEEL BASKET
- MAGNETICALLY SHIELDED
- GOOD FOR HOME THEATER, MULTIMEDIA, CAR APPLICATION

4" PP FULL RANGE



DIAPHRAGM MTL	Structured pp
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	4 Ω
DCR IMPEDANCE	3.8 Ω
SENSITIVITY 1W/1m	87 dB
FREQUENCY RESPONSE	63 - 17 Hz
FREE AIR RESONANCE	63 Hz
VOICE COIL DIAMETER	25.4 mm
AIR GAP HEIGHT	2.5 mm
RATED POWER INPUT	40 W
MAXIMUM POWER INPUT	80 W
FORCE FACTOR, BL	3.5 TM
MAGNET WEIGHT (oz)	Neodymium
MOVING MASS	3.85g
FERROFLUID ENHANCED	No
SUSPENSION COMPLIANCE	1642.8370 MN ⁻¹
EFFECTIVE PISTON AREA	0.0057 M ²
Levc	0.0410mh
Zo	38.6677ohm.
X-max	3.4mm
Vas	7.58 Litr.
Qts	0.44
Qms	4.46